



Audio Cable

AES EBU Digital Audio Plenum Cable

UL Type CMP (UL) c(UL)

Single - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M		
SDS124P CMP (UL) C(UL)	1	24 (7x32) TC 23.8Ω/Mft	Foam FEP		100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft	0.160	4.06	11.00	36.08	21.00	68.88
			0.020	0.51							
			Color Code: White & Black								
Dual - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M		
SDS224P CMP (UL) C(UL)	2	24 (7x32) TC 23.8Ω/Mft	Foam FEP		100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft	0.330 x 0.160	8.38 x 4.06	11.00	36.08	21.00	68.88
			0.020	0.51							
			Color Code: White & Black								
4 Pair - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M		
SDS424P CMP (UL) C(UL)	4	24 (7x32) TC 23.8Ω/Mft	Foam Polyethylene		100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft	0.368	9.35	11.00	36.08	21.00	68.88
			0.020	0.51							
			Color Code: White & Black								

PRODUCT CONSTRUCTION

Conductor:
• Copper per ASTM B-3

Insulation:
• Foam FEP

Shield:
• 100% Foil + Drain

Jacket:
• Plenum PVC

APPLICATIONS
• AES Digital Audio
• Extended Bandwidth Analog Audio
• Time Code
• Studio Interconnect, Permanent Installation, or Portable Cables

PACKAGING (Single & Dual)
• 500 ft. or 1000 ft. Boxes & Reels

PACKAGING (4 Pair)
• 500 ft. or 1000 ft. Reels

JACKET COLOR
• Single - White
• Dual - White
• 4 Pair - White

