



Audio Cable

AES EBU Digital Audio Riser Cable

UL Type CMR (UL) c(UL)

Single - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M	21.00	68.88
			Foam Polyethylene			100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft					
SDS124R CMR (UL) C(UL)	1	24 (7x32) TC 23.8Ω/MR	0.021	0.53		0.180	4.57	11.00	36.08		
			Color Code: White & Black								
Dual - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M	21.00	68.88
			Foam Polyethylene			100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft					
SDS224R CMR (UL) C(UL)	2	24 (7x32) TC 23.8Ω/MR	0.021	0.53		0.370 x 0.180	9.40 x 4.57	11.00	36.08		
			Color Code: White & Black								
4 Pair - AES EBU Digital Audio Cable											
CATALOG NUMBER UL TYPE	Number of Pairs	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
			Inches	mm		Inches	mm	PF/FT	PF/M	21.00	68.88
			Foam Polyethylene			100% Foil +22 AWG (7x30) TC Drain 15.3Ω/Mft					
SDS424R CMR (UL) C(UL)	4	24 (7x32) TC 23.8Ω/MR	0.021	0.53		0.620	15.75	11.00	36.08		
			Color Code: White & Black								

PRODUCT CONSTRUCTION

Conductor:
• Copper per ASTM B-3

Insulation:
• Foam Polyethylene

Shield:
• 100% Foil + Drain

Jacket:
• PVC

APPLICATIONS

- AES Digital Audio
- Extended Bandwidth Analog Audio
- Time Code
- Studio Interconnect, Permanent Installation, or Portable Cables

PACKAGING (Single & Dual)

- 500 ft. or 1000 ft. Boxes & Reels

PACKAGING (4 Pair)

- 500 ft. or 1000 ft. Reels

JACKET COLOR

- Single - Black & Purple
- Dual - Purple
- 4 Pair - Purple

