



## High-Grade Analog Audio Cable

# Single-Pair, Shielded, Riser or Plenum 22 AWG & 20 AWG

NEC Type CMR or CMP (UL) c(UL)

### 22 AWG, HIGH-GRADE ANALOG AUDIO RISER CABLE

CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
		Inches	mm		Inches	mm	PF/FT	PF/M	PF/FT	PF/M
		SAHS122R  CMR (UL) C(UL)	22 (7x30) BC 16.3Ω/Mft		SR-PVC 0.008   0.20		100% Foil + 24 AWG (7x32) TC Drain 27.0Ω/Mft	0.128	3.25	44.56
		Color Code: Red & Black								

### 22 AWG, HIGH-GRADE ANALOG AUDIO PLENUM CABLE

CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
		Inches	mm		Inches	mm	PF/FT	PF/M	PF/FT	PF/M
		SAHS122P  CMP (UL) C(UL)	22 (7x30) BC 16.3Ω/Mft		PVC 0.008   0.20		100% Foil + 24 AWG (7x32) TC Drain 27.0Ω/Mft	0.128	3.25	45.55
		Color Code: Red & Black								

### 20 AWG, HIGH-GRADE ANALOG AUDIO RISER CABLE

CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
		Inches	mm		Inches	mm	PF/FT	PF/M	PF/FT	PF/M
		SAHS120R  CMR (UL) C(UL)	20 (7x28) BC 10.2Ω/Mft		SR-PVC 0.007   0.18		100% Foil + 22 AWG (7x30) TC Drain 16.9Ω/Mft	0.135	3.43	53.17
		Color Code: Red & Black								

### 20 AWG, HIGH-GRADE ANALOG AUDIO PLENUM CABLE

CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD	
		Inches	mm		Inches	mm	PF/FT	PF/M	PF/FT	PF/M
		SAHS120P  CMP (UL) C(UL)	20 (7x28) BC 10.2Ω/Mft		PVC 0.008   0.20		100% Foil + 22 AWG (7x30) TC Drain 16.9Ω/Mft	0.139	3.53	50.87
		Color Code: Red & Black								

### PRODUCT CONSTRUCTION

#### Conductor:

- Stranded bare copper per ASTM B-3

#### Insulation:

- CMR - Premium-grade S-R PVC
- CMP - Plenum PVC

#### Shield:

- 100% Overall Foil Shield
- Stranded Tinned Copper Drain

#### Jacket:

- CMR - Premium PVC
- CMP - Plenum PVC

#### JACKET COLOR

- CMR - Gray
- CMP - White

#### APPLICATIONS

- Microphone or Line Level Balanced Analog Audio
- Patchbay, Rack, or Console Permanent Installation Wiring
- Ideal for Extended Distance Runs

#### PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels

