



Audio Cable

Indoor/Outdoor Direct Burial - OFC Speaker Cable
 UL Type CM, CL3 & PLTC (UL) c(UL)

CATALOG NUMBER	Number of Conductors	AWG TYPE DCR	Insulation Wall		NOMINAL O.D.		Jacket	Jacket Color	UL Type
			Inches	mm	Inches	mm			
SSPUB162	2	16 (65x34) Oxygen-Free BC 4.0Ω/Mft	PVC		0.236	5.99	PVC	White	CM, CL3 & PLTC
			0.010	0.25					
			Color Code: Red & Black						
SSPUB164	4	16 (65x34) Oxygen-Free BC 4.0Ω/Mft	PVC		0.272	6.91	PVC	White	CM, CL3 & PLTC
			0.010	0.25					
			Color Code: Black, White, Red & Green						
SSPUB142	2	14 (105x34) Oxygen-Free BC 2.5Ω/Mft	PVC		0.268	6.81	PVC	White	CM, CL3 & PLTC
			0.012	0.30					
			Color Code: Red & Black						
SSPUB144	4	14 (105x34) Oxygen-Free BC 2.5Ω/Mft	PVC		0.312	7.92	PVC	White	CM, CL3 & PLTC
			0.012	0.30					
			Color Code: Black, White, Red & Green						

PRODUCT CONSTRUCTION

Conductor:
 • Copper per ASTM B-3

Insulation:
 • PVC

Jacket:
 • PVC

FEATURES & BENEFITS

- 99.999% OFC Copper
- Wide Frequency Response
- Two- and Four-Conductor Versions
- Direct Burial and Sunlight Resistant
- UL Rated for Permanent Installation

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels

