



Audio Cable

Indoor/Outdoor Direct Burial Speaker Cable

UL Type CM or CL3 (UL) c(UL)

CATALOG NUMBER	Number of Conductors	AWG TYPE DCR	Insulation Wall		NOMINAL O.D.		Jacket	Jacket Color	UL Type
			Inches	mm	Inches	mm			
SSUB162	2	16 (65x34) BC 4.0Ω/Mft	PVC		0.222	5.64	PVC	White	CM & CL3
			0.010	0.25					
			Color Code: Red & Black						
SSUB164	4	16 (65x34) BC 4.0Ω/Mft	PVC		0.250	6.35	PVC	White	CM & CL3
			0.009	0.23					
			Color Code: Black, White, Red & Green						
SSUB142	2	14 (41x30) BC 2.5Ω/Mft	PVC		0.252	6.40	PVC	White	CL3
			0.011	0.28					
			Color Code: Red & Black						
SSUB144	4	14 (41x30) BC 2.5Ω/Mft	PVC		0.297	7.54	PVC	White	CL3
			0.012	0.30					
			Color Code: Black, White, Red & Green						
SSUB122	2	12 (105x32) BC 1.5Ω/Mft	PVC		0.306	7.77	PVC	White	CM & CL3
			0.011	0.28					
			Color Code: Red & Black						
SSUB124	4	12 (105x32) BC 1.5Ω/Mft	PVC		0.364	9.25	PVC	White	CM & CL3
			0.011	0.28					
			Color Code: Black, White, Red & Green						

PRODUCT CONSTRUCTION

Conductor:
• Copper per ASTM B-3

Insulation:
• PVC

Jacket:
• PVC

FEATURES & BENEFITS

- High-Strand Bare Copper
- Wide Frequency Response
- Two- and Four-Conductor Versions
- Direct Burial and Sunlight Resistant
- UL Rated for Permanent Installation

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels

