



Audio Cable

Microphone Cable

Multi-Conductor, Rubber, Braid Shield

Microphone Cable: Rubber				NOM. JACKET THICKNESS		NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN CONDUCTOR & SHIELD	
CATALOG NUMBER UL TYPE	AWG TYPE DCR	NOM. INSULATION THICKNESS		Inches	mm	Inches	mm	PF/FT	PF/M	PF/FT	PF/M
		Inches	mm								
SMR202	20 (26/34) TC 10.1 Ω/Mft	EPDM		0.035	0.89	0.270	6.86	25.55	83.80	53.17	174.40
		0.020	0.51								

NO. OF CONDUCTORS	COLOR
1	Black
2	White

PRODUCT CONSTRUCTION

- Conductor:**
- 20 AWG fully annealed stranded tinned copper per ASTM B-33
- Insulation:**
- Premium-grade, color coded EPDM
 - Temperature Rating: 90°C
 - Color per chart below

- Shield:**
- 80% tinned copper braid

- Jacket:**
- Rubber, black
 - Temperature range: -40°C to +90°C

- Applications**
- Control circuits
 - Broadcast and studio applications
 - Audio interconnects
 - Suggested voltage rating: 300 Volts

- Features**
- Impact and abrasion resistant
 - Stranded conductors for superior flexibility

- Compliances**
- RoHS Compliant Directive 2002/95/EC

- Packaging**
- 500 ft. or 1000 ft. Boxes & Reels

