



**Audio Cable**

# 22 & 24 AWG, Premium Analog Audio Cables

UL Type CMR or CMP (UL) c(UL)

22 AWG, PREMIUM ANALOG AUDIO RISER CABLE											
CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD		
		Inches	mm		Inches	mm	PF/FT	PF/M			
		Polyethylene									
SAPS122R  CMR (UL) C(UL)	22  (7x30) TC 15.3Ω/Mft	0.008	0.20	100% Foil + 22 AWG (7x30) TC Drain 15.3Ω/Mft	0.138	3.51	34.00	111.52	62.00	203.36	
		Color Code: Red & Black									
22 AWG, PREMIUM ANALOG AUDIO PLENUM CABLE											
CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD		
		Inches	mm		Inches	mm	PF/FT	PF/M			
		Halar									
SAPS122P  CMP (UL) C(UL)	22  (7x30) TC 15.3Ω/Mft	0.010	0.25	100% Foil + 22 AWG (7x30) TC Drain 15.3Ω/Mft	0.134	3.40	28.00	91.84	52.00	170.56	
		Color Code: Red & Black									
24 AWG, PREMIUM ANALOG AUDIO RISER CABLE											
CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD		
		Inches	mm		Inches	mm	PF/FT	PF/M			
		Polyethylene									
SAPS124R  CMR (UL) C(UL)	24  (7x32) TC 23.8Ω/Mft	0.008	0.20	100% Foil + 24 AWG (7x32) TC Drain 23.8Ω/Mft	0.115	2.92	28.00	91.84	51.00	167.28	
		Color Code: Red & Black									
24 AWG, PREMIUM ANALOG AUDIO PLENUM CABLE											
CATALOG NUMBER UL TYPE	AWG TYPE DCR	Insulation Wall		Shield Type DCR	NOMINAL O.D.		CAPACITANCE BETWEEN CONDUCTORS		CAPACITANCE BETWEEN ONE CONDUCTOR & OTHER TIED TO SHIELD		
		Inches	mm		Inches	mm	PF/FT	PF/M			
		Halar									
SAPS124P  CMP (UL) C(UL)	24  (7x32) TC 23.8Ω/Mft	0.010	0.25	100% Foil + 24 AWG (7x32) TC Drain 23.8Ω/Mft	0.129	3.28	26.00	85.28	48.00	157.44	
		Color Code: Red & Black									

**PRODUCT CONSTRUCTION**

**Conductor:**  
• Copper per ASTM B-33

**Insulation:**  
• CMR - Polyethylene  
• CMP - Halar

**Shield:**  
• 100% Foil Shield  
• Stranded Drain

**Jacket:**  
• CMR - Premium PVC  
• CMP - Plenum PVC

**APPLICATIONS**

- Microphone or Line Level Balanced Analog Audio
- Patchbay, Rack, or Console Permanent Installation Wiring
- Ideal for Extended Distance Runs

**PACKAGING**

- 500 ft. or 1000 ft. Boxes & Reels

**JACKET COLOR**

- CMR - Black, White & Red
- CMP - White

