



Speaker and Control Cable

Multi-Conductor, Shielded, Riser

NEC Type CL3R (UL) and/or NEC Type CMR (UL) c(UL)

RISER CABLE - SR-PVC INSULATION, PVC JACKET

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	Nom. Insulation Wall		Nom. Jacket Wall		NOMINAL O.D.		NEC TYPE
				Inches	mm	Inches	mm	Inches	mm	
22 AWG CONDUCTORS										
SSS222R	2	22	7/30	0.008	0.20	0.015	0.38	0.125	3.18	CL3R & CMR
SSS224R	4	22	7/30	0.008	0.20	0.015	0.38	0.144	3.66	CL3R & CMR
20 AWG CONDUCTORS										
SSS202R	2	20	7/28	0.007	0.18	0.015	0.38	0.142	3.61	CL3R & CMR
SSS204R	4	20	7/28	0.007	0.18	0.015	0.38	0.171	4.34	CL3R & CMR
18 AWG CONDUCTORS										
SSS182R	2	18	7/26	0.008	0.20	0.015	0.38	0.159	4.04	CL3R & CMR
SSS184R	4	18	7/26	0.008	0.20	0.015	0.38	0.184	4.67	CL3R & CMR
16 AWG CONDUCTORS										
SSS162R	2	16	19/.0117	0.009	0.23	0.015	0.38	0.183	4.65	CL3R & CMR
SSS164R	4	16	19/.0117	0.009	0.23	0.015	0.38	0.219	5.56	CL3R & CMR
14 AWG CONDUCTORS										
SSS142R	2	14	19/.0147	0.010	0.25	0.015	0.38	0.217	5.51	CL3R
SSS144R*	4	14	19/.0147	0.010	0.25	0.015	0.38	0.254	6.45	CL3R
12 AWG CONDUCTORS										
SSS122R	2	12	19/.0185	0.011	0.28	0.015	0.38	0.257	6.53	CL3R
SSS124R*	4	12	19/.0185	0.011	0.28	0.015	0.38	0.304	7.72	CL3R

PRODUCT CONSTRUCTION

Conductor:

- Stranded bare copper per ASTM B-3

Insulation:

- CMR - Premium-grade S-R PVC

Shield:

- 100% Foil Shield
- Stranded Tinned Copper Drain

Jacket:

- CMR - Premium PVC

Jacket Color:

- CMR - Gray

APPLICATIONS

- Power-limited control circuits
- Wiring of the following systems:
 - Intercom
 - Security
 - Audio
 - Background Music

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels
- *Reels only

Color Code Chart

NO OF. COND.	COLOR
1	Black
2	Red
3	White
4	Green

