

Speaker and Control Cable

Multi-Conductor, Unshielded, Plenum

NEC Type CL3P (UL) and/or NEC Type CMP (UL) c(UL)

PLENUM CABLE - PVC INSULATION, PVC JACKET

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	Nom. Insulation Wall		Nom. Jacket Wall		NOMINAL O.D.		NEC TYPE
				Inches	mm	Inches	mm	Inches	mm	
22 AWG CONDUCTORS										
SSU222P	2	22	7/30	0.008	0.20	0.015	0.38	0.120	3.05	CL3P & CMP
SSU224P	4	22	7/30	0.008	0.20	0.015	0.38	0.139	3.53	CL3P & CMP
20 AWG CONDUCTORS										
SSU202P	2	20	7/28	0.008	0.20	0.015	0.38	0.134	3.40	CL3P & CMP
SSU204P	4	20	7/28	0.008	0.20	0.015	0.38	0.156	3.96	CL3P & CMP
18 AWG CONDUCTORS										
SSU182P	2	18	7/26	0.008	0.20	0.015	0.38	0.156	3.96	CL3P & CMP
SSU184P	4	18	7/26	0.008	0.20	0.015	0.38	0.180	4.57	CL3P & CMP
16 AWG CONDUCTORS										
SSU162P	2	16	19/.0117	0.008	0.20	0.015	0.38	0.174	4.42	CL3P & CMP
SSU164P	4	16	19/.0117	0.008	0.20	0.015	0.38	0.205	5.21	CL3P & CMP
14 AWG CONDUCTORS										
SSU142P	2	14	19/.0147	0.010	0.25	0.015	0.38	0.212	5.38	CL3P
SSU144P*	4	14	19/.0147	0.010	0.25	0.015	0.38	0.247	6.27	CL3P
12 AWG CONDUCTORS										
SSU122P	2	12	19/.0185	0.011	0.28	0.015	0.38	0.252	6.40	CL3P
SSU124P*	4	12	19/.0185	0.011	0.28	0.015	0.38	0.298	7.57	CL3P
10 AWG CONDUCTORS (AUDIO ONLY)										
SSU102P*	2	10	65/28	0.012	0.30	0.017	0.43	0.305	7.75	CL2P
8 AWG CONDUCTORS (AUDIO ONLY)										
SSU082P*	2	8	65/26	0.012	0.30	0.017	0.43	0.358	9.09	CL2P

PRODUCT CONSTRUCTION

Conductor:
• Stranded bare copper per ASTM B-3

Insulation:

• CMP - Plenum PVC

Jacket:

• CMP - Plenum PVC

Jacket Color:

• CMP - White (Natural)

APPLICATIONS

- Power-limited control circuits
- Wiring of the following systems:
 - Intercom
 - Security
 - Audio
 - Background Music

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels
- *Reels only

Color Code Chart

NO. OF COND.	COLOR
1	Black
2	Red
3	White
4	Green