

Speaker and Control Cable

Multi-Conductor, Unshielded, Riser

NEC Type CL3R (UL) and/or NEC Type CMR (UL) c(UL)

RISER CABLE - SR-PVC INSULATION, PVC JACKET				Nom. Insulation Wall		Nom. Jacket Wall		NOMINAL O.D.		NEC TYPE
CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	Inches	mm	Inches	mm	Inches	mm	
22 AWG CONDUCTORS										
SSU222R	2	22	7/30	0.008	0.20	0.015	0.38	0.122	3.10	CL3R & CMR
SSU224R	4	22	7/30	0.008	0.20	0.015	0.38	0.144	3.66	CL3R & CMR
20 AWG CONDUCTORS										
SSU202R	2	20	7/28	0.007	0.18	0.015	0.38	0.134	3.40	CL3R & CMR
SSU204R	4	20	7/28	0.007	0.18	0.015	0.38	0.142	3.61	CL3R & CMR
18 AWG CONDUCTORS										
SSU182R	2	18	7/26	0.008	0.20	0.015	0.38	0.154	3.91	CL3R & CMR
SSU184R	4	18	7/26	0.008	0.20	0.015	0.38	0.180	4.57	CL3R & CMR
16 AWG CONDUCTORS										
SSU162R	2	16	19/.0117	0.009	0.23	0.015	0.38	0.178	4.52	CL3R & CMR
SSU164R	4	16	19/.0117	0.009	0.23	0.015	0.38	0.210	5.33	CL3R & CMR
14 AWG CONDUCTORS										
SSU142R	2	14	19/.0147	0.010	0.25	0.015	0.38	0.212	5.38	CL3R
SSU144R*	4	14	19/.0147	0.010	0.25	0.015	0.38	0.249	6.32	CL3R
12 AWG CONDUCTORS										
SSU122R	2	12	19/.0185	0.011	0.28	0.015	0.38	0.252	6.40	CL3R
SSU124R*	4	12	19/.0185	0.011	0.28	0.015	0.38	0.298	7.57	CL3R
10 AWG CONDUCTORS (AUDIO ONLY)										
SSU102R*	2	10	65/28	0.012	0.30	0.017	0.43	0.305	7.75	CL2R
8 AWG CONDUCTORS (AUDIO ONLY)										
SSU082R*	2	8	65/26	0.012	0.30	0.017	0.43	0.358	9.09	CL2R

PRODUCT CONSTRUCTION

Conductor:
• Stranded bare copper per ASTM B-3

Insulation:
• CMR - Premium-grade S-R PVC

Jacket:
• CMR - Premium PVC

Jacket Color:
• CMR - Gray

APPLICATIONS

- Power-limited control circuits
- Wiring of the following systems:
 - Intercom
 - Security
 - Audio
 - Background Music

PACKAGING

- 500 ft. or 1000 ft. Boxes & Reels
- *Reels only

Color Code Chart

NO OF COND.	COLOR
1	Black
2	Red
3	White
4	Green